


## Specifications



## General

A component of the Wybron Infotrace Series of Products

Control and power for the following Wybron products:

- NEXERA LX Luminaires
- CXI IT Color Changers
- COLORAM IT Color Changers
- ECLIPSE IT SHUTTER/ECLIPSE IT IRIS Dowsers
- FORERUNNER Color Changers

Front & rear LEDs indicating signal and power

Integrated stainless steel safety cable

Truss or rack mountable; free standing

.063" aluminum sheet metal construction

RJ-45 connector for ethernet input

Six 4 pin XLR connector for power and data

Two 5 pin XLR connector for 2 DMX universes of output

Made in USA

## Power/Data\*

Accepts all standard voltages worldwide  
(100-132 VAC 50/60 Hz and 170-240 VAC 50/60 Hz)

Sends/passes 24v DC and DXM/RDM

## XLR Connector Pin Out

XLR Pin #	Function	Conductor Size
1	Ground	14 AWG
2	Data +	22 AWG
3	Data -	22 AWG
4	24 Volts DC	14 AWG

*\*Not Compatible with Ram II Power Supplies*

## Control Inputs

Artnet over Ethernet

ANSI E1.31-Interoperable ethernet transport  
for DMX 512A

## Control Outputs

Uses DMX512-A Protocol

Infotrace features available using  
ANSI E1.20 - 2006 Remote Device Management  
over USITT DMX512 standard

## Parameters and features selectable with Infotrace/RDM:

Device Label

Firmware Upgrade

## Infotrace/RDM feedback information

Type of Device


Voltage Output Sensor

Device Drop Warning

## Specifications

### Dimensions & Weights

NET IT PS-600 Model 20610



Weight: 7.90 lbs./3.58kg

**NET IT PS-600**  
2-Port Node/  
Power Supply

### Equipment Compatibility\*\*

The following is a chart of compatibility and capacity of the NET IT PS-600 2-port Node/Power Supply and the companion devices.

2-port Node/600W Power Supply		NET IT PS-600	
Model		20610	
Output Power		600W	
Maximum devices per Power Supply			
Description	Model	Head Ft.	
CXI IT 7.5"	87200	1500	24
CXI IT 4"	84560	1500	24
CXI IT Lg Format	816050	750	9
CXI IT 12"	812210	500	8
CXI IT 8-light	816130	750	12
CXI IT Mariner	87220	1500	24
CXI IT MultiPar	87240	1000	18
NEXERA LX (tungsten)	2560LX, 2570LX, 2640LX	1500	32
NEXERA LX (CDM)	2580LX, 2600LX, 2650LX	1500	24
COLORAM IT 7.5"	87110	1500	24
COLORAM IT 4"	84520	1500	24
COLORAM IT 10"	810100	1000	16
COLORAM IT Lg Frmt	816090	1000	24
COLORAM IT 15"	815010	1000	24
COLORAM IT 8-light	816080	1000	20
AQUARAM IT 7.5"	87080	1000	20
AQUARAM IT Lg Frmt	85000	1000	24
ECLIPSE IT SHUTTER 1K	89001	1500	32
ECLIPSE IT SHUTTER 2K	811010	1500	32
ECLIPSE IT SHUTTER Lg Frmt	817000	1500	32
ECLIPSE IT IRIS 1K	87250	1500	24
ECLIPSE IT IRIS 2K	812020	1500	24
ECLIPSE IT IRIS 24"	823020	750	12
FORERUNNER 4"	4540	n/a	64
FORERUNNER 7"	7140	n/a	64

<sup>1</sup> Some watts/unit numbers are rounded up/down \*\* The above information assumes devices are on different channels and all move simultaneously

### Ordering Information

NET IT PS-600 Power Supply	
Model	Description
20610	2-port Node 600W Power Supply
NET IT PS-600 Power Supply Accessories	
7042-XX	Power/Data Cable (XX=Length)*

\* Available in 3', 5', 10', 15', 25', 50', 75', & 100' lengths

**WYBRON**

Advancing The Art Of Lighting